



Alkali Resisting Primer

PRODUCT DATA

Description:

An off-white primer of very low lead content for brush or spray application. Designed for cementitious type surfaces with an alkaline nature.

Area of use:

Interior and exterior

Substrate s:

Concrete, cement, plaster, block work etc.

Packing:

2.5 Litre

Physical Constants:

Colour:	Off white
Finish:	Matt
Volume solids:	50%
Theoretical spreading rate:	15 m ² sq. metres per litre
Flash point:	38°C
Specific gravity:	1.25
Dry to touch:	4 - 6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush/roller Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.