



Aluminium Gloss

PRODUCT DATA

Description:

A superior alkyd topcoat providing a bright silver finish.

Area of use:

Interior and exterior.

Substrates:

Metal surfaces, woodwork, fibre-boards, etc.

Packing:

2.5 and 5 Litre

Physical Constants:

Colour:	Aluminium
Finish:	High gloss
Volume solids:	42%
Theoretical spreading rate:	15 m ² sq. metres per litre
Flash point:	38°C
Specific gravity:	1.1
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.