



## Aluminium Primer

### PRODUCT DATA

---

#### Description:

A multi purpose primer. Particularly valuable in minimising "bleeding" on the more resinous types of timber. Formulated to seal knots and prevent resin seepage, This primer is ideal for both interior and exterior applications. The original self-knotting primer which for many years has proved the most successful product of its kind.

#### Area of use:

Interior and exterior.

#### Substrates:

Wood and metal

#### Packing:

2.5 Litre

#### Physical Constants:

Colour:	Aluminium
Finish:	Matt
Volume solids:	48%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.25
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush	Conventional spray	Airless spray
Thinner:	White Spirit		
Cleaning of tools:	White Spirit		

#### Surface condition:

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. In order to maintain its protective properties Aluminium Primer should not be rubbed down before applying for coatings.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.