



Anti Slip PU Floor Paint

PRODUCT DATA

Description

Anti slip polyurethane floor paint based on a high quality resin system with a very fine textured finish. It is suitable for application to most surfaces and will provide a hard wearing, water and oil resistant finish, this product is ideal for general walkways, factory and garage floors.

***Important Note: This product has anti-slip properties and therefore provides slip resistance, however, it is not possible to guarantee a totally non-slip surface.**

Sealing / Priming

It is only necessary to seal a porous substrate such as new or bare concrete. A sealer coat is achieved by adding 10% white spirit to the paint. Please note new concrete floors can only be painted after 6-8 weeks.

Area of use

Interior and exterior (not suitable for all exterior applications)

Substrates

Concrete, stone and wooden floors

Packing

5 litre and 20 litres (supplied as 4 x 5L tins)
20 litre drums (min order for drums is 12 x 20L)

Physical Constants

Colours: Red-04039, Green 14C39, Grey 00A05, Blue 20D45 and Black

Finish: Semi gloss

Volume solids: 50%

Theoretical spreading rate: 12 - 15 sq. metres per litre (depending on surface)

Flash point: 38°C

Specific gravity: 1.4

Dry to touch: 2 - 4 hours (20°C)

Over-coating time: 16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method: Brush or roller

Thinner: White Spirit

Cleaning of tools: White Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

For additional guidance please contact your local Technical Sales Representative. Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.