

Anti Ruginie



PRODUCT DATA

Description:

High quality one coat anti-rust metal paint. Based on Micaceous Iron Oxide.

Area of use:

Interior and exterior.

Substrates:

Ferrous metal

Packing:

5 Litre

Physical Constants:

Colours:	Grey and black
Finish:	Matt
Volume solids:	50%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.3
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush	Conventional spray	Airless spray
Thinner:	White Spirit		
Cleaning of tools:	White Spirit		

Surface condition:

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.