

Anti Slip PU Floor Paint



PRODUCT DATA

Description:

Hard wearing polyurethane one pack paint designed to seal and colour concrete floors. Provides anti-slip* properties for pedestrian traffic areas. Petrol and oil resistant, this product is ideal for general walkways, factory and garage floors. Excellent durability. A special order product, please discuss your requirements with your local representative.

***Important Note: This product has anti-slip properties and therefore provides slip resistance, however, it is not possible to guarantee a totally non slip surface.**

Area of use:

Interior and exterior.

Substrates:

Concrete floors

Packing:

5 Litre, 20 Litre (supplied as 4x5L tins)
20 Litre Drum (minimum order for drums is 8 x 20L)

Physical Constants:

Colours:	Red, Green, Grey, Blue, Black
Finish:	Semi gloss
Volume solids:	50%
Theoretical spreading rate:	12 - 15 sq. metres per litre (depending on surface)
Flash point:	38°C
Specific gravity:	1.4
Dry to touch:	2 - 4 hours (20°C)
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush/roller Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.