

Aqualac HD



PRODUCT DATA

Description:

Heavy-duty water based floor lacquer. Quick drying, non-toxic, low odour non-yellowing easy to apply, giving a durable scuff resistant finish.

Area of use:

Heavy traffic wood flooring

Substrates:

Wood

Packing:

5 Litres

Physical Constants:

Colour:	Clear
Finish:	Gloss Semi Matt (on request in batch quantities)
Volume solids:	44%
Theoretical spreading rate:	14 – 16 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.07
Dry to touch:	15 – 20 minutes
Overcoating time:	2 – 3 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Conventional spray Airless spray Flooring applicator
Thinner:	Water
Cleaning of tools:	Water

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393