



## Aqualac Joint Filler

### PRODUCT DATA

---

#### Description:

Quick drying joint filler for use prior to applying aqualac floor finish. After sanding, sawdust can be mixed with joint filler to fill larger joints to give a natural finish.

#### Area of use:

Wooden floors

#### Substrates:

Wood

#### Packing:

2.5 Litres and 5 Litres

#### Physical Constants:

Colour:	Clear
Finish:	Semi Matt
Volume solids:	30%
Theoretical spreading rate:	15 sq.metres per litre
Flash point:	12°C
Specific gravity:	0.97
Dry to touch:	5 – 10 minutes
Overcoating time:	1 – 2 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Pallet Knife or Scraper
Thinner:	Cellulose Thinners
Cleaning of tools:	Cellulose Thinners

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.