

Aqualac PU



PRODUCT DATA

Description:

The ultimate heavy-duty water based floor lacquer. Quick drying, non-toxic, low odour non-yellowing easy to apply, giving a durable scuff resistant finish. Ideal for high quality furniture, dance floors, sports halls and very heavy foot traffic areas.

Area of use:

Heavy traffic wood flooring and wood furniture.

Substrates:

Wood

Packing:

5 Litres

Physical Constants:

| | |
|-----------------------------|---|
| Colour: | Clear |
| Finish: | Gloss Semi Matt (on request in batch quantities) |
| Volume solids: | 44% |
| Theoretical spreading rate: | 14 – 16 sq.metres per litre |
| Flash point: | N/A |
| Specific gravity: | 1.07 |
| Dry to touch: | 15 – 20 minutes |
| Overcoating time: | 2 – 3 hours |

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

| | |
|---------------------|--|
| Application method: | Brush Conventional spray Airless spray Flooring applicator |
| Thinner: | Water |
| Cleaning of tools: | Water |

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.