



Asipo Algicidal Treatment

PRODUCT DATA

Description:

A clear single pack water-borne algicidal wash. For use as a surface biocide. A very effective biocide to protect against mould, lichens, mosses and algae. Long term protection against re-growth. Simple to apply. Can be over-coated with most conventional paints. For further protection overcoat the treated areas with Asipo paints.

Directions for use:

Dilute with 4 parts water to 1 part Asipo Algicidal Treatment.
Apply liberally with a brush, sponge or cloth and wipe off (before allowing it to dry).
Stubborn areas may require a further application or try leaving the treatment to work longer before wiping off. Clean the treated areas with clean water or a mild cleaning solution.

For use on a wide variety of external building substrates. Suitable for use as an algicidal wash on patios, external paving, roof tiles/substrates, decking, brick & block work.

Area of use:

Internal and External

Substrates:

Concrete, render, brick, general masonry and roofing substrates, including internal wall and ceiling tiles.

Packing:

5 Litre

Physical Constants:

Colour:	Clear
Finish:	N/A
Volume solids:	N/A
Theoretical spreading rate:	15 - 20 sq. metres per litre (dependant on porosity)
Flash point:	N/A
Specific gravity:	1.0 – 1.02
Dry to touch:	2 hours (20°C)
Over-coating time:	6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush / Sponge / Cloth / Spray
Thinner: Dilute with water as instructed
Cleaning of tools: Water

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.