



## Asipo All Weather Coating

### PRODUCT DATA

---

#### Description:

A Pliolite based reinforced masonry coating. This product is flexible and micro-porous, allowing the surface to breath while providing a rain-proof barrier, along with excellent self-cleaning properties. It's easy to apply, and provides a long lasting durable finish. A unique blend of resins ensures maximum penetrate and adhesion to even the most difficult masonry surfaces, without the need for a separate primer.

All Asipo products are formulated to incorporate active biocides. These biocides are non toxic and provide long term protection against damaging mould and algae attack.

#### Area of use:

Exterior, wall areas

#### Substrates:

Cementitious, render, block work etc.

#### Packing:

5 Litres

#### Physical Constants:

Colours::	White, Black (other colours on request)
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	10 sq. metres per litre
Flash point:	42°C
Specific gravity:	1.3
Dry to touch:	4 hours (20°C)
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush/roller Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.