

Asipo Barrier



PRODUCT DATA

Description:

Designed to form a barrier within the plaster or rendered surface on walls or ceilings to prevent Mould spores re-appearing.

Area of use:

Internal and External

Substrates:

Brick, plaster and rendered surfaces

Packing:

5 Litre

Physical Constants:

Colour:	Clear
Finish:	N/A
Volume solids:	N/A
Theoretical spreading rate:	8 - 10 sq. metres per diluted litre
Flash point:	N/A
Specific gravity:	1.0 – 1.01
Dry to touch:	30 minutes
Over-coating time:	1 hour

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Sponge or Cloth
Thinner:	N/A
Cleaning of tools:	Water

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.