

Asiposeal



## PRODUCT DATA

---

### Description:

Non-silicone based, single pack solvent-borne protective coating. Clear coating used to seal external masonry areas. Proven effective to stop water penetration. Provides long-term protection against surface contamination by air-borne spores.

### Area of use:

Exterior

### Substrates:

Concrete, render, brick and general masonry

### Packing:

5 Litre

### Physical Constants:

Colour: Clear

Finish: Semi Gloss

Volume solids: 12%

Theoretical spreading rate: 10 - 20 sq. metres per litre (dependant on porosity)

Flash point: 38°C

Specific gravity: 0.85

Dry to touch: 2 hours (20°C)

Overcoating time: 6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### Application Details:

Application method: Brush / Spray

Thinner: White Spirit

Cleaning of tools: White Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393