



## BLACK MAGIC

### PRODUCT DATA

---

#### Description:

BLACK MAGIC adheres to metal, plastic and glass. It provides a very tough finish with minimal brush marks. It is very easy to apply and normally provides a very tough finish in just one coat. BLACK MAGIC also contains a built in rust converter to neutralise rust. Rust is converted to a polymer that is absorbed into the BLACK MAGIC. Rust is encapsulated into the BLACK MAGIC and becomes a stable part of the tough coating. BLACK MAGIC provides ongoing protection against further rusting. This product is an environmentally friendly, water-based (quick drying and low odour) high performance coating.

#### Area of use:

Interior, Exterior

#### Substrates:

Metal, Plastic and Glass

#### Packing:

1 litre and 250 ml

#### Physical Constants:

Colour:	Black
Finish:	Satin
Volume solids:	40%
Theoretical spreading rate:	8-12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.20
Dry to touch:	30 minutes
Over-coating time:	4-6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush
Thinner:	Water
Cleaning of tools:	Water

**Surface Condition:** Ensure surface is free from all flaking material, dust, dirt and grease. Do not apply in temperatures below 10°C

*Please refer to the Material Safety Data Sheet for further information.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.