



Boiled Linseed Oil

PRODUCT DATA

Description:

A natural vegetable oil similar to raw linseed oil but with drying qualities. Used for feeding dry wood or for sealing unglazed terracotta tiles.

Area of use:

Interior and exterior

Substrates:

Wood/unglazed terracotta tiles

Packing:

5 Litres

Physical Constants:

Colour:	Amber
Finish:	Semi Gloss
Volume solids:	N/A
Theoretical spreading rate:	15 – 20 sq.metres per litre
Flash point:	N/A
Specific gravity:	0.91
Dry to touch:	8 – 12 hours
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Cloth
Thinner:	N/A
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.