

# PRODUCT INFORMATION



## The Classic Range of Wood Finishing Products



This picture is for illustration purposes only. Some product packaging & labels have now changed.

**CLASSIC WAX** An economical Pine enhancing treatment derived from our years of experience producing quality wood finishing products for the Pine furniture trade. Classic Wax is toluene-free, safe and easy to use, giving an excellent shine. Classic Wax is especially formulated to achieve a professional finish to wood with a minimum amount of effort.

**CLASSIC TEAK OIL** A natural wood treatment for external and internal use. Ideal for garden furniture, bare timber and enhancing the natural colour of teak oil. Produces a satin, matt finish.

**CLASSIC FURNITURE CLEANER** A traditional recipe made from mixes of traditional oils and solvents. Classic Furniture Cleaner allows you to clean old wax and crime without damaging original hard finishes. Ideal for use on stair banisters, where grime has collected over the years.

**CLASSIC BROWN FRENCH POLISH** A traditional French polish made from natural shellac and industrial methylated spirit. Used on top of Shellac Sanding Sealer to give a warm, golden brown, gloss finish. Mainly for use on dark wood surfaces such as Mahogany.

**CLASSIC SHELLAC SANDING SEALER** A traditional sealer made from natural shellac and industrial methylated spirit. A suitable product for use under shellac based finishes such as French or Button Polish. Ideal on surfaces that are open grained. Quick drying, and ideally suited for use under Classic Wax to produce a higher shine.

**CLASSIC LIMING WAX** A smooth white paste wax that produces a white grained look on wood. Particularly effective on Oak and other open grained woods. Apply directly onto wood, working the wax well into the grain. Simply remove excess wax with Classic Wax clear. Allow to go tacky, then simply buff with a soft cloth to achieve a gloss finish.

**CLASSIC KNOTTING SOLUTION** A traditional knotting solution made from pure shellac and industrial methylated spirits. For use on knots prior to priming and undercoating to prevent resinous sap bleeding through paint or varnish film.

**CLASSIC TERRACOTTA WAX** Tiles should first be sealed with boiled Linseed Oil. Apply wax with a cloth or brush, working well into the tiles. Leave for 3-4 minutes and polish with a cloth or buffing machine. Additional applications will enhance the true colour of the tiles and give a more desirable finish.

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.