



## Concrete Sealer

### PRODUCT DATA

---

#### Description:

Clear coating used to seal concrete floors and block paving driveways. Petrol and oil resistant. Based on a thermoplastic acrylic resin to give flexibility and UV resistance. Easy to apply and quick drying.

#### Area of use:

Interior and exterior.

#### Substrates:

Concrete floors and driveways

#### Packing:

5 Litre

#### Physical Constants:

Colour:	Clear
Finish:	Gloss
Volume solids:	30%
Theoretical spreading rate:	16 sq. metres per litre
Flash point:	23°C
Specific gravity:	0.9
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush
Thinner:	Xylene
Cleaning of tools:	Xylene

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.