

FLAG Antifouling Primer



PRODUCT DATA

Description:

Antifouling primer gives a solid base-coat prior to the application of FLAG Antifouling

Area of use:

Boat hulls

Substrates:

GRP, wood, steel and ferro cement.

Packing:

2.5 Litre

Physical Constants:

Colour:	White
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	10 sq.metres per litre
Flash point:	42°C
Specific gravity:	1.30
Dry to touch:	2 hours
Overcoating time:	6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Conventional spray Airless spray Roller
Thinner:	Flagship Antifouling Thinners
Cleaning of tools:	Flagship Antifouling Thinners

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.