



## FLAG CopperQuick Antifouling

### PRODUCT DATA

---

#### **Description:**

A low friction semi-hard antifouling based on a PTFE resin and an extremely fine grade of copper. CopperQuick is easier to scrub and being a relatively 'thin film' will not create 'build-up' like many conventional antifouling. This product is pre-mixed (only requires good stirring to ensure homogeneity before use) and easy to apply. The quick drying nature of this product allows for minimal 'out of water' time. If required, extra coats can be applied and re-launching can be achieved inside a day. 2 or 3 coats are normally required dependent on the base condition. Performance PTFE is self-priming and can be applied over any previous PTFE based or hard antifouling. Traditional (softer) antifouling should be removed prior to the application of Performance PTFE. Particularly suitable for fast power or sail craft in low to medium fouling areas

#### **Area of use:**

Boat hulls below the waterline.

#### **Substrates:**

GRP, wood, steel and ferro cement. Not suitable for aluminum or galvanised surfaces.

#### **Packing:**

1 litre and 2.5 litres

#### **Physical Constants:**

Colour:	Copper
Finish:	Semi-matt
Volume solids:	47%
Theoretical spreading rate:	12 sq.metres per litre
Flash point:	42°C
Specific gravity:	1.16
Dry to touch:	1-2 hours
Over-coating time:	4 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method:	Sponge or short hair roller. Conventional spray. Airless spray.
Thinner:	FLAG Antifouling Thinners
Cleaning of tools:	FLAG Antifouling Thinners

**Surface condition:** The surface should be smooth, stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.