



## PRODUCT DATA

---

### Description:

A superior alkyd topcoat. The product is ideally suited for kitchens and bathrooms, doors, window frames, furniture and woodwork in general. Also ideal for metal surfaces. Designed for top-class work where the highest standards of finish, durability and colour retention are required.

### Area of use:

Interior and exterior.

### Substrates:

Metal surfaces, woodwork, fibre-boards, etc.

### Physical Constants:

Colours: Black and White or Special Order

Finish: High gloss

Volume solids: 40%

Theoretical spreading rate: 15 sq. metres per litre

Flash point: 38°C

Specific gravity: 1.1

Dry to touch: 6 hours (20°C)

Overcoating time: 16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### Application Details:

Application method: Brush/roller Conventional spray Airless spray

Thinner: White Spirit

Cleaning of tools: White Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats. Undercoat may be required.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.