



Flagspeed Machinery Enamel

PRODUCT DATA

Description:

High quality polyurethane enamel easy to apply. Excellent opacity, durability, and washability. General purpose product with rapid drying properties which permit short down times when painting machinery and rapid handling of components after painting.

Area of use:

Interior and exterior

Substrates:

Industrial Machinery and metalwork

Packing:

5 Litre

Physical Constants:

Colours: White and black, colours on request

Finish: Gloss

Volume solids: 42%

Theoretical spreading rate: 15 sq. metres per litre

Flash point: 38°C

Specific gravity: 1.2

Dry to touch: 2 - 4 hours (20°C)

Overcoating time: 16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush/roller Conventional spray Airless spray

Thinner: White Spirit

Cleaning of tools: White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats. Undercoat may be required.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.