



## Flag Tile Paint (CLEAR)

### PRODUCT DATA

---

#### Description:

A protective clear top-coat for use over Flag Tile Paint. Designed to provide additional durability for the protection of commercial areas.

#### Substrates:

Ceramic Tiles

#### Physical Constants:

Colours:	Clear
Finish:	Gloss
Volume solids:	46%
Theoretical spreading rate:	20 sq. metres per litre
Flash point:	38°C
Specific gravity:	0.93
Dry to touch:	2 hours (20°C)
Overcoating time:	4-8 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush/Roller <i>Recommended rollers are short pile sheepskin or synthetic fibre Foam rollers are not recommended</i>
Thinner:	White Spirit
Cleaning of tools:	White Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.