

Polyurethane Floor Paint



PRODUCT DATA

Description:

Hard wearing polyurethane one pack paint designed to seal and colour concrete floors, enabling you to keep it clean and tidy. Petrol and oil resistant, this product is ideal for factory and garage floors. Excellent durability.

Area of use:

Interior and exterior.

Substrates:

Concrete floors

Packing:

5 Litre, 20 Litre (supplied as 4x5L tins)
20 Litre Drum (minimum order for drums is 8 x 20L)

Physical Constants:

Colours:	Red, Green, Grey, Blue, Black (Clear available as special order)
Finish:	Semi gloss
Volume solids:	48%
Theoretical spreading rate:	12 - 15 sq. metres per litre (depending on surface)
Flash point:	38°C
Specific gravity:	1.10 - 1.20
Dry to touch:	2 - 4 hours (20°C)
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush/roller Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.