



Heat Resisting Pale Polish

PRODUCT DATA

Description:

High quality pale polish for use where heat resistance is a requirement. Gives a hard durable finish.

Area of use:

Interior

Substrates:

Wood

Packing:

5 Litres

Physical Constants:

Colour:	Pale Amber
Finish:	Gloss
Volume solids:	30%
Theoretical spreading rate:	18 sq.metres per litre
Flash point:	18°C
Specific gravity:	0.89
Dry to touch:	10 – 15 minutes
Over-coating time:	30 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Use a shellac sanding sealer prior to using heat resisting pale polish.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.