



## Liming Wax

### PRODUCT DATA

---

#### Description:

Paste wax to give a limed finish grain, particularly on oak doors or cabinets. Buff to a gloss finish.

#### Area of use:

Furniture

#### Substrates:

Wood

#### Packing:

250mls

#### Physical Constants:

|                             |                           |
|-----------------------------|---------------------------|
| Colour:                     | White                     |
| Finish:                     | Gloss                     |
| Volume solids:              | 30%                       |
| Theoretical spreading rate: | 6 – 8 sq.metres per litre |
| Flash point:                | 38°C                      |
| Specific gravity:           | 1.1                       |
| Dry to touch:               | 30 minutes                |
| Overcoating time:           |                           |

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

|                     |              |
|---------------------|--------------|
| Application method: | Cloth        |
| Thinner:            | N/A          |
| Cleaning of tools:  | White Spirit |

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.