

Premium Smooth Masonry Paint



PRODUCT DATA

Description:

A high quality obliterating masonry paint. Manufactured using a blend of premium quality resins for extra strength and flexibility. Provides a weather resistant matt finish that can be washed down. Water-based, so brushes are easily rinsed out. Part of the FLAG Premium range, Extra Opacity, Premium Quality and Extra Strong. No primer required simply thin with up to 10% water if applying on bare or absorbent surfaces.

Area of use:

Interior and exterior.

Substrates:

General masonry, concrete, plaster and wood etc.

Packing:

5 Litres, 15 Litres

Physical Constants:

Colours: White, Sand Stone

Finish: Matt

Volume solids: 50%

Theoretical spreading rate: 8 - 12 sq. metres per litre

Flash point: N/A

Specific gravity: 1.27 – 1.29

Dry to touch: 2 hours (20°C)

Overcoating time: 4 - 6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush/roller Conventional spray Airless spray

Thinner: Water

Cleaning of tools: Water

Surface condition:

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

Please refer to the Material Safety Data Sheet for further information.

For additional guidance please contact your local Technical Sales Representative.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.