



Polyurethane Varnish

PRODUCT DATA

Description

A tough polyurethane clear varnish is based on a good quality resin system giving excellent durability, it is a hardwearing and suitable for wood flooring, furniture etc.

Area of use

Interior or exterior

Substrates

Wood

Packing

1 litre, 2.5 litres and 5 litres (min batch 100 litres)

Physical Constants

Colour:	Clear
Finish:	Gloss/Eggshell
Volume solids:	42%
Theoretical spreading rate:	16 sq.meters per litre
Flash point:	38°C
Specific gravity:	0.92
Dry to touch:	2 – 4 hours
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, conventional or airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.
--------------------------	--

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.