



Pure Shellac Varnish

PRODUCT DATA

Description

Pure shellac varnish is a heavy duty finish mainly used where a traditional French polish is not required. It has excellent water resistance and when dried is free from chemicals and solvents. Suitable for use on packing boxes and furniture.

Area of use

Interior and exterior

Substrates

Wood

Packing

500ml and 5 litres

Physical Constants

Colour:	Dark Amber
Finish:	Gloss
Volume solids:	36%
Theoretical spreading rate:	16 sq.metres per litre
Flash point:	18°C
Specific gravity:	0.88
Dry to touch:	20 minutes
Overcoating time:	30 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.