



## Pure Shellac Varnish

### PRODUCT DATA

---

#### Description:

Heavy-duty shellac finish used where a traditional french polish finish is not required. Used as a protective coating on packing boxes.

#### Area of use:

Interior and exterior

#### Substrates:

Wood

#### Packing:

5 Litre

#### Physical Constants:

Colour:	Dark Amber
Finish:	Gloss
Volume solids:	36%
Theoretical spreading rate:	16 sq.metres per litre
Flash point:	18°C
Specific gravity:	0.88
Dry to touch:	20 minutes
Overcoating time:	30 minutes

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.