



PRODUCT DATA

Description:

Specifically developed to provide instant waterproofing for leaking roofs, an all-weather product that can be applied even in damp conditions. Roofix 20/10 can be used to repair specific areas which are leaking or totally waterproof an entire roof. This product is multi-purpose and can be utilised on a wide variety of problem areas.

A single pack elastomeric acrylic based (non bitumastic) compound, with built in Draylon fibre reinforcement, providing excellent flexibility and durability. Provides exceptional adhesion to virtually any roofing material. Roofix 20/10 does not require special primers, and can provide long term protection in excess of 10 years.

Area of use:

Exterior: roof areas, gutters, flashing, bay window and porch areas

Substrates:

A wide variety of roofing materials

Packing:

1 Litre, 5 Litre and 20 Litre (supplied as 4x5L tins)
20 Litre Drum (minimum order for drums is 8 x 20L)

Physical Constants:

| | |
|-----------------------------|--|
| Colours: | Black, white and grey (solar reflective silver on request) |
| Finish: | Semi gloss |
| Volume solids: | 48% |
| Theoretical spreading rate: | 1 sq. metres per litre |
| Flash point: | 42°C |
| Specific gravity: | 1.1 kg/litre |
| Dry to touch: | 16 hours (20°C) |
| Curing time: | 2 - 3 days |

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

| | |
|---------------------|--------------------------------------|
| Application method: | Brush/soft broom, trowel or spreader |
| Thinner: | White Spirit |
| Cleaning of tools: | White Spirit |

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Should not be applied in the rain or when rain is likely. Pooled water must be removed before application.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.