
PRODUCT DATA

Description:

Specifically developed to provide instant waterproofing for leaking roofs, and gutters etc. Roofix M is an all-weather product that can be applied even in damp conditions. Suitable for repairing specific areas (patches) which are leaking or totally waterproof an entire roof. This product is multi-purpose and multisurface. Roofix M can be utilised on a wide variety of problem areas.

A single pack elastomeric acrylic based (non bitumastic) compound providing excellent flexibility and durability. Provides exceptional adhesion to virtually any roofing material. Roofix M does not require special primers, and can provide long term protection in excess of 10 years.

Area of use:

Exterior: roof areas, gutters, flashing, bay window and porch areas

Substrates:

A wide variety of roofing materials (including metal, wood, felt, plastic, OSB & PVC)

Packing:

1 and 23 Kg

Physical Constants:

Colours:	Black
Finish:	Semi gloss
Volume solids:	48%
Theoretical spreading rate:	1 kilo per sq. metre
Flash point:	42°C
Specific gravity:	1.1 kg/litre
Dry to touch:	16 hours (20°C)
Curing time:	2 - 3 days

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush/soft broom, trowel or spreader
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Should not be applied in the rain or when rain is likely. Pooled water must be removed before application.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.