



Shellac Sanding Sealer

PRODUCT DATA

Description:

A shellac sanding sealer made from a blend of shellacs and zinc stearate which is ideal for sealing new or stripped wood prior to waxing and french polishing. Ease of sanding ensures a perfect finish.

Area of use:

Interior

Substrates:

Wood

Physical Constants:

Colour:	Transparent
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	18°C
Specific gravity:	0.87
Dry to touch:	5 - 10 minutes (20°C)
Over-coating time:	15 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.