



## Vinyl Satin Emulsion

### PRODUCT DATA

---

#### Description:

A vinyl copolymer emulsion paint giving a subdued gloss or satin finish with outstanding toughness and durability. Intended for the decoration of walls and ceilings where maximum washability and resistance to wear and tear is required.

#### Area of use:

Interior

#### Substrates:

Cementitious, plaster, block work etc.

#### Physical Constants:

Colour:	White and Magnolia other colours on request
Finish:	Satin
Volume solids:	42%
Theoretical spreading rate:	12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.3
Dry to touch:	2 - 4 hours (20°C)
Overcoating time:	4 – 6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Brush/roller Conventional spray Airless spray
Thinner:	Water
Cleaning of tools:	Water

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.